

View Online at <https://aerobasegroup.com/nsn/4720-01-321-4426>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.594 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel nut, inverted flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

24 2nd end

**Burst Test Pressure:**

20000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

60.000 inches

**Thread Series Designator:**

Uns 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0