NSN 4720-01-321-4436

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-321-4436

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 1.000 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.230 inches |
| Minimum Inside Bending Radius: |
| 7.380 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.312 inches 1st end |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.312 inches 1st end |
| Bolt Hole Quantity: |
| 4 1st end |
| Flange Length: |
| 1.562 inches 1st end |
| Flange Width: |
| 1.562 inches 1st end |
| Connection Style: |
| Plain 1st end |
| Bolt Hole Diameter: |
| 0.290 inches 1st end |
| End Flange Construction: |
| Solid 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Plain face flange 1st end |
| Burst Test Pressure: |
| 3200.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure: |
| 800.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 10.750 inches |
| Flange Style: |
| Rectangular (includes square) 1st end |

NSN 4720-01-321-4436

Nonmetallic Hose Assembly - Page 2 of 2



| Med | dia | For | Whi | ich | Desi | ianed: |
|-----|-----|-----|-----|-----|------|---------|
| | ula | | | | | ıuııcu. |

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0