

View Online at <https://aerobasegroup.com/nsn/4720-01-323-4269>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

2.562 inches 2nd end

**Flange Thickness:**

0.234 inches 2nd end

**Outside Diameter:**

1.750 inches

**Minimum Inside Bending Radius:**

11.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

356.0

**Bolt Hole Quantity:**

4 2nd end

**Flange Outside Diameter:**

3.094 inches 2nd end

**Connection Style:**

Plain 2nd end

**Bolt Hole Diameter:**

0.266 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer rubber impregnated braided steel wire and 2nd layer braided cotton cord and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 1st end

**Outer Covering Environmental Protection:**

Oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.250 inches

**Flange Style:**

Round w/ bolt holes 2nd end

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0