## NSN 4720-01-323-5901

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-323-5901

Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.875 inches
Minimum Inside Bending Radius:
6.500 inches
Quick Disconnect Size:
0.375 inches 2nd end
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

## NSN 4720-01-323-5901

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0