

View Online at <https://aerobasegroup.com/nsn/4720-01-323-7047>

Cross Sectional Shape:

Round

Inside Diameter:

1.812 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.359 inches 2nd end

Flange Thickness:

0.297 inches 2nd end

Outside Diameter:

2.219 inches

Minimum Inside Bending Radius:

13.500 inches

Angle Between Rigid Elbow Fittings In Deg:

0.0

Center To Center Distance Between Bolt Holes Along Length:

3.359 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Outside Diameter:

3.953 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.328 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided steel wire and 2nd layer rubber impregnated braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

350.0 pounds per square inch

Hydrostatic Test Pressure:

700.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.000 inches

Flange Style:

Round w/ bolt holes 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0