NSN 4720-01-324-9362

Cross Sectional Shape:

Round

Unjs 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-324-9362

Thread Class: 3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.850 inches
Minimum Inside Bending Radius: 2.880 inches
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 2nd end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.719 inches 2nd end
Seat Angle:
8.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.500 inches working
Thread Series Designator:

NSN 4720-01-324-9362

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	h	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0