Nonmetallic Hose Assembly - Page 1 of 2



resistant

View Online at https://aerobasegroup.com/nsn/4720-01-327-0095

~	reas Sectional Shaney
	ross Sectional Shape:
	hread Class:
	b 1st end
	hread Direction:
	ight-hand 1st end
	nside Diameter:
-	.212 inches
	empurature Rating:
	65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
	outside Diameter:
	etween 0.360 inches and 0.390 inches
	linimum Inside Bending Radius:
-	.500 inches
	nd Application:
	ockheed corporation c130h aircraft
	connection Style:
	wivel nut, flareless 1st end
	nd Connection Design:
	traight 1st end
С	connection Type:
Т	hreaded internal tube 1st end
В	urst Test Pressure:
1	2000.0 pounds per square inch
L	ayer Composition And Location:
С	outer layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
3	000.0 pounds per square inch
Т	hread Size:
0	.438 inches 1st end
S	eat Angle:
1	2.0 degrees 1st end
Н	ydrostatic Test Pressure:
6	000.0 pounds per square inch
C	outer Covering Environmental Protection:
E	thylene glycol resistant and fuel resistant and heat resistant and oil resistant and solvent resistant and vibration
lr	nside Surface Condition:
S	mooth
N	leasuring Method And Length:
1	3.500 inches working
т	hread Series Designator:
U	njf 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

81343-as115 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0