Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-327-1848

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
1.000 inches	
Fempurature Rating:	
40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Dutside Diameter:	
1.500 inches	
Inimum Inside Bending Radius:	
2.000 inches	
End Application:	
2320-01-272-5028	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Fhreaded external pipe 1st end	
Burst Test Pressure:	
3000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber	
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Thread Size:	
1.500 inches 1st end	
Hydrostatic Test Pressure:	
1000.0 pounds per square inch	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
18.000 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
J/a	
Jnit Of Measure:	
-	

## NSN 4720-01-327-1848

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

