Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-327-2840

-	
	Sectional Shape:
Round	
Thread	
3b 1st e	
	Direction:
-	and 1st end
	Diameter:
0.125 in	
-	ature Rating:
	grees fahrenheit single response and 450.0 degrees fahrenheit single response
	e Diameter:
0.250 in	
	m Inside Bending Radius:
1.500 in	
	tion Style:
Swivel n	nut flare 1st end
End Co	nnection Design:
Straight	1st end
Connec	tion Type:
Threade	ed internal tube 1st end
Feature	s Provided:
Electros	tatic discharge capability
Burst To	est Pressure:
12000.0	pounds per square inch
Layer C	composition And Location:
Outer lag	yer braided corrosion resistant steel wire
Maximu	Im Operating Pressure:
1500.0 p	pounds per square inch
Thread	Size:
0.750 in	ches 1st end
Seat An	igle:
37.0 deg	grees 1st end
Hydrost	tatic Test Pressure:
3000.0 p	pounds per square inch
Vacuum	n In Torr:
50.8	
Inside S	Surface Condition:
Smooth	
Measuri	ing Method And Length:
8.250 in	ches
Thread	Series Designator:
Unjf 1st	end

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

