Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-327-7664

Cro	ss Sectional Shape:
Rou	-
Thr	ead Class:
3b 1	1st end
Thr	ead Direction:
Rigł	ht-hand 1st end
Insi	de Diameter:
0.34	14 inches
Ten	npurature Rating:
-65.	0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Out	side Diameter:
0.54	17 inches
Min	imum Inside Bending Radius:
2.50	00 inches
Cor	nnection Style:
Swi	vel nut, flareless 1st end
End	Connection Design:
Stra	aight 2nd end
Cor	nnection Type:
Thre	eaded internal tube 1st end
Bur	st Test Pressure:
800	.0 pounds per square inch
Lay	er Composition And Location:
Out	er layer braided corrosion resistant steel wire
Max	kimum Operating Pressure:
200	.0 pounds per square inch
Thr	ead Size:
0.56	62 inches 2nd end
Sea	it Angle:
12.0) degrees 1st end
Hyd	Irostatic Test Pressure:
400	.0 pounds per square inch
Flo	w Angle:
45.0) degrees 1st end
Insi	de Surface Condition:
Smo	poth
Меа	asuring Method And Length:
12.1	125 inches
Thre	ead Series Designator:
Unjf	f 1st end
She	elf Life:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0