NSN 4720-01-327-7673

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-327-7673

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.535 inches and 0.595 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Identical Burst Test Pressure:
Burst Test Pressure:
Burst Test Pressure: 10500.0 pounds per square inch
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability:
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location:
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure:
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size:
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle:
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 12.0 degrees 1st end
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 12.0 degrees 1st end Inside Surface Condition:
Burst Test Pressure: 10500.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer braided corrosion resistant steel wire err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 12.0 degrees 1st end Inside Surface Condition: Smooth

Inner conveying tube material-plastic, tetrafluoroethylene

NSN 4720-01-327-7673

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0