NSN 4720-01-329-1311

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aeroba

View Online at https://aerobasegroup.com/nsn/4720-01-329-1311	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.406 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response	
Outside Diameter:	
0.585 inches	
Minimum Inside Bending Radius:	
4.620 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and alcohol resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.000 inches working

Thread Series Designator:

Unf 1st end

NSN 4720-01-329-1311

Nonmetallic Hose Assembly - Page 2 of 2



S	pe	cifi	cat	ion	Data:

96906-ms8005 government standard

Specification Or Standard:

8 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0