## NSN 4720-01-329-7240

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-329-7240

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.730 inches
Minimum Inside Bending Radius:
3.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Smooth  Measuring Method And Length:
Measuring Method And Length:
Measuring Method And Length: 41.000 inches working
Measuring Method And Length: 41.000 inches working Thread Series Designator:
Measuring Method And Length: 41.000 inches working Thread Series Designator: Unjf 1st end
Measuring Method And Length: 41.000 inches working Thread Series Designator: Unjf 1st end Specification Data:

## NSN 4720-01-329-7240

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0