

View Online at <https://aerobasegroup.com/nsn/4720-01-329-7252>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.343 inches

Minimum Inside Bending Radius:

2.000 inches

End Application:

General motors, allison gas turbine, generator set, 501k

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and alcohol resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.500 inches

Thread Series Designator:

Unf 1st end

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0