Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-329-9836

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.812 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and alcohol resistant and solvent resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches working
Thread Series Designator:
Un 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

96906-ms8005 government standard

Specification Or Standard:

12 size

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

