NSN 4720-01-330-0601

33.500 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-330-0601

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.125 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response	
Outside Diameter:	
1.390 inches	
Minimum Inside Bending Radius:	
11.000 inches	
End Application:	
Allison gas turbine generator set, mdl.501k	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
4000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
1.625 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Outer Covering Environmental Protection:	
Acid resistant and mildew resistant and fuel resistant and oil resistant and solvent resistant and vibration resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	

NSN 4720-01-330-0601

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series	Designator:
Un 1st end	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0