

View Online at <https://aerobasegroup.com/nsn/4720-01-330-2458>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.239 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

1.560 inches

**Minimum Inside Bending Radius:**

3.500 inches

**End Application:**

General motors corp. Generator set, model 501k

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thread Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

4000.0 pounds per square inch

**Layer Composition And Location:**

1st layer polytetrafluoroethylene impregnated glass fiber and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

1.625 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

30.000 inches working

**Thread Series Designator:**

Un 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0