## NSN 4720-01-330-6558

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-330-6558

Round
Inside Diameter:
1.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Flange Thickness:
0.312 inches 1st end
Outside Diameter:
1.790 inches
Minimum Inside Bending Radius:
3.375 inches
Bolt Hole Quantity:
4 1st end
Flange Outside Diameter:
3.094 inches 1st end
End Application:
Allison gas turbine generator set, mdl.501k
Connection Style:
Raised 1st end
Bolt Hole Diameter:
0.281 inches 1st end
Raised Face Height:
0.010 inches 1st end
Raised Face Diameter:
2.880 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
Connection Type:
Raised face flange 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer polytetrafluoroethylene impregnated glass fiber and outer layer rubber impregnated wire
Maximum Operating Pressure:
150.0 pounds per square inch
Hydrostatic Test Pressure:
300.0 pounds per square inch

## NSN 4720-01-330-6558

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Convoluted
<b>Measuring Method And Length:</b>
29.000 inches
Flange Style:
Round w/ bolt holes 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0