

View Online at <https://aerobasegroup.com/nsn/4720-01-330-8135>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.344 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.766 inches

Minimum Inside Bending Radius:

5.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-8788, size 6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Socket aluminum alloy 2nd end

Fitting Component And Surface Treatment:

Nut cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

14000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

42.500 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

96906-ms28759 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-8788 spec.