

View Online at <https://aerobasegroup.com/nsn/4720-01-330-9439>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.312 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.469 inches

**Minimum Inside Bending Radius:**

4.000 inches

**End Application:**

Allison gas turbine generator set, mdl.501k

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.562 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Acid resistant and mildew resistant and fuel resistant and oil resistant and solvent resistant and vibration resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

68.000 inches

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0