

View Online at <https://aerobasegroup.com/nsn/4720-01-332-0823>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.630 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.910 inches

Minimum Inside Bending Radius:

6.000 inches

End Application:

Falk corp., gear assembly. For 3035-mvl-e unit on u.S.Navy tugs

Connection Style:

Swivel, plain 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.688 inches

Media For Which Designed:

Air single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0