

View Online at <https://aerobasegroup.com/nsn/4720-01-332-0823>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.630 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.910 inches

**Minimum Inside Bending Radius:**

6.000 inches

**End Application:**

Falk corp., gear assembly. For 3035-mvl-e unit on u.S.Navy tugs

**Connection Style:**

Swivel, plain 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided textile yarn and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

11.688 inches

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0