Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-332-5960

View Online at https://aerobasegroup.com/nsn/4720-01-332-5960
Cross Sectional Shape:
Round
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Special Features:
Assembly consists of basic hose assembly per ms8000e240a with nipple per an816-4 and quick disconnect on first end and elbow fitting
attached to second end per ms20822-4 and quick disconnect
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0