## NSN 4720-01-332-6899

18.250 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-332-6899

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.188 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response                                  |
| Outside Diameter:  |
| 0.343 inches   |
| Minimum Inside Bending Radius:   |
| 2.000 inches   |
| End Application:   |
| Boeing f-18 aircraft   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Features Provided:   |
| Electrostatic discharge capability and reusable end fittings   |
| Burst Test Pressure:   |
| 12000.0 pounds per square inch   |
| Layer Composition And Location:  |
| Outer layer braided corrosion resistant steel wire   |
| Maximum Operating Pressure:  |
| 1500.0 pounds per square inch  |
| Thread Size:   |
| 0.375 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 3000.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Acid resistant and mildew resistant and fuel resistant and oil resistant and solvent resistant and vibration resistant |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |

## NSN 4720-01-332-6899

Nonmetallic Hose Assembly - Page 2 of 2



Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0