NSN 4720-01-333-8195

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-333-8195

Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.250 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
0.590 inches			
Minimum Inside Bending Radius:			
4.000 inches			
End Application:			
3930-01-305-2111			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
20000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided steel wire and outer layer braided steel wire			
Maximum Operating Pressure:			
5000.0 pounds per square inch			
Thread Size:			
0.375 inches 1st end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
10000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
21.000 inches			
Media For Which Designed:			

Fuel/oil, hydrocarbon single response

NSN 4720-01-333-8195

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hroad	Series	I Jaciui	12t∩r•
ııııcau	061163	Desidi	iatoi.

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0