## NSN 4720-01-334-3780

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-334-3780

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
1.707 inches
Minimum Inside Bending Radius:
14.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.875 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and alcohol resistant and ethylene glycol resistant and solvent resistant and acid resistant and oxidation
resistant
Inside Surface Condition:
Smooth

30.000 inches working

**Measuring Method And Length:** 

## NSN 4720-01-334-3780

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0