NSN 4720-01-337-7200

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-337-7200

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
1.812 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
2.219 inches				
Minimum Inside Bending Radius:				
13.250 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 1st end				
Burst Test Pressure:				
1400.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided wire and 2nd layer braided cotton cord and outer layer rubber impregnated braided cotton cord				
Maximum Operating Pressure:				
350.0 pounds per square inch				
Thread Size:				
2.500 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
700.0 pounds per square inch				
Outer Covering Environmental Protection:				
Oil resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
151.000 inches working				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

NSN 4720-01-337-7200

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0