## NSN 4720-01-337-7202

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-337-7202

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.812 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
2.219 inches
Minimum Inside Bending Radius:
13.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided cotton cord and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
2.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
700.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
41.000 inches working
Media For Which Designed:

## NSN 4720-01-337-7202

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0