NSN 4720-01-337-7215

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-337-7215

Cross Sectional Shape:						
Round						
Thread Class:						
2b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.375 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response						
Outside Diameter:						
0.690 inches						
Minimum Inside Bending Radius:						
5.000 inches						
End Application:						
3930-01-305-2111, truck forklift						
Connection Style:						
Swivel nut flare 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Nonskive						
Burst Test Pressure:						
9000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
2250.0 pounds per square inch						
Thread Size:						
0.562 inches 1st end						
Seat Angle:						
37.0 degrees 1st end						
Hydrostatic Test Pressure:						
4500.0 pounds per square inch						
Outer Covering Environmental Protection:						
Abrasion resistant and oil resistant and weatherproof						
Inside Surface Condition:						

84.000 inches

Measuring Method And Length:

Smooth

NSN 4720-01-337-7215

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0