

View Online at <https://aerobasegroup.com/nsn/4720-01-338-0499>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.590 inches

Minimum Inside Bending Radius:

4.000 inches

End Application:

FORK-LI-FTT-RUCK

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

54.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0