NSN 4720-01-338-2139

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-338-2139

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.688 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response				
Outside Diameter:				
0.938 inches				
Minimum Inside Bending Radius:				
4.500 inches				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Reusable end fittings				
Burst Test Pressure:				
3750.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1000.0 pounds per square inch				
Thread Size:				
1.067 inches 1st end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
2000.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
20.750 inches				
Media For Which Designed:				

Fuel/oil, hydrocarbon single response

NSN 4720-01-338-2139

Nonmetallic Hose Assembly - Page 2 of 2



-	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0