

View Online at <https://aerobasegroup.com/nsn/4720-01-338-4359>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

1.062 inches

Minimum Inside Bending Radius:

9.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nonskive and reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

12400.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3100.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6200.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0