

View Online at <https://aerobasegroup.com/nsn/4720-01-339-7865>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-15.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.430 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Thready Qty Per Inch (tpi):

24 and 18 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided synthetic cord and 2nd layer braided synthetic cord and 2nd layer molded rubber, synthetic

Thread Size:

0.438 inches 1st end

Seat Angle:

30.0 degrees 1st end

Outer Covering Environmental Protection:

Alcohol resistant and hydraulic solution resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.220 inches

Special Features:

Second end fitting has a invert flare seat angle 42.0 deg

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0