

View Online at <https://aerobasegroup.com/nsn/4720-01-339-7865>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b and 2a 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.125 inches

**Temperature Rating:**

-15.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.430 inches

**Connection Style:**

Inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal and external tube 2nd end

**Thready Qty Per Inch (tpi):**

24 and 18 2nd end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided synthetic cord and 2nd layer braided synthetic cord and 2nd layer molded rubber, synthetic

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Outer Covering Environmental Protection:**

Alcohol resistant and hydraulic solution resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

25.220 inches

**Special Features:**

Second end fitting has a invert flare seat angle 42.0 deg

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0