## NSN 4720-01-339-7870



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-339-7870 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.810 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Orange **Connection Style:** Inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyamide cord and outer layer molded polyurethane **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 7000.0 pounds per square inch **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 13.000 inches

Thread Series Designator:

Unf 1st end

## NSN 4720-01-339-7870

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0