Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-340-6501

Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches 275.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded infernal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 205.0 pounds per square inch Straight 1st end Straight 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 205.0 poinds per square inch Maximum Operating Pressure: 37.0 degrees 1st end Straight 1st end Straight 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 200.0 pounds per square inch Thread Surface Condition: Convolted Messuring Method And Length: 31.00 inches Thread Surface Surface Unit of Measure: Vint Of Measure: <t< th=""><th>Cross Sectional Shape:</th><th></th></t<>	Cross Sectional Shape:	
Thread Class: J3b 1st end Thread Class: J3b 1st end Thread Class: J3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: Z75.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimun Inside Bending Radius: 0.625 inches Connection Style: Straight 1st end Connection Dosign: Straight 1st end Connection Dosign: Straight 1st end Burst Test Pressure: St0.0 pounds per square inch Maximum Operating Pressure: 25.0 degrees 1st end End Connection Ist end Stat Angle: J7.0 degrees 1st end End Connection Ist end Stat Angle: J7.0 degrees 1st end Stat Angle: J7.0 degrees Ist end Inside Surface Condition: Convoluted Measuring Method And Length: J1.000 inches Thread Series Designator: Unjf 1st end Sheft Life: Na Filg: Na Filg: Na Filg: Na		
Sh 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.330 inches Minimum Inside Bending Radius: 0.635 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Maximum Operating Tressure: 250.0 pounds per square inch Maximum Operating Pressure: 260.0 pounds per square inch Maximum Operating Pressure: 260.0 pounds per square inch Maximum Operating Pressure: 20.0 pounds per square inch		
Thread Direction: Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Thread dimernal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Maximum Quest 1st end Burst Test Pressure: 250.0 pounds per square inch Maximum Quest 1st end Burst Test Pressure: 250.0 pounds per square inch Maximum Quest 1st end Burst Test Pressure: 250.0 pounds per square inch Maximum Quest 1st end Burst Test Pressure: 250.0 pounds per square inch Maximum Quest 1st end Steat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif of Measure: Unif of Measure: Wind Umasure:		
Right-hand 1st end Inside Diameter: 0.313 inches Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.500 inches Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: Na Unit Of Measure:		
Inside Diameter: 0.313 inches Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 0.530 inches Connection Style: Swisel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: Va Unif Of Measure: Demilitarization: No		
0.313 inches Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Burst Test Pressure: 250.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Straight 1st end Strate Condition: Convoltad Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0	
Tempurature Rating: 275.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 00.00 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch 250.0 pounds per square inch 250.0 pounds per square inch 250.0 pounds per square		
275.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Steat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: Na Unit Of Measure: Thread Size: Demilitarization: No Fig:		
Outside Diameter: 0.530 linches Minimum Inside Bending Radius: 0.625 linches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 linches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Minimum Inside Bending Radius: 0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	Outside Diameter:	
0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.530 inches	
0.625 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Minimum Inside Bending Radius:	
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.625 inches	
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Style:	
Straight 1 st end Connection Type: Threaded internal tube 1 st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 250.0 pounds per square inch Thread Size: 0.562 inches 1 st end Seat Angle: 37.0 degrees 1 st end Seat Angle: 37.0 degrees 1 st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1 st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Swivel nut flare 1st end	
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	End Connection Design:	
Threaded internal tube 1st end Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fijg:	Straight 1st end	
Burst Test Pressure: 500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Type:	
500.0 pounds per square inch Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Threaded internal tube 1st end	
Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Burst Test Pressure:	
250.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	500.0 pounds per square inch	
Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Operating Pressure:	
0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	250.0 pounds per square inch	
Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Size:	
37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.562 inches 1st end	
Inside Surface Condition: Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Seat Angle:	
Convoluted Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	37.0 degrees 1st end	
Measuring Method And Length: 31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inside Surface Condition:	
31.000 inches Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Convoluted	
Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Measuring Method And Length:	
Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	31.000 inches	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Filg:	Unjf 1st end	
Unit Of Measure: Demilitarization: No Filg:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Filg:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A542a0	Fiig:	
	A542a0	