## NSN 4720-01-340-7058

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-340-7058 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.770 inches **Minimum Inside Bending Radius:** 4.625 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and 2nd layer braided textile yarn and outer layer molded rubber **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 15.000 inches Media For Which Designed:

**Thread Series Designator:** 

Fuel/oil, hydrocarbon single response

Unf 1st end

## NSN 4720-01-340-7058

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0