Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-341-0029

View Online at https://aerobasegroup.com/nsn/4720-01-341-0029
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
1.140 inches
Minimum Inside Bending Radius:
7.375 inches
End Application:
4920-01-218-4171
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and alcohol resistant and solvent resistant and acid resistant and oxida

Fuel resistant and oil resistant and alcohol resistant and solvent resistant and acid resistant and oxidation resistant

Inside Surface Condition:

Smooth



Measuring Method And Length:

52.000 inches working

Thread Series Designator:

Un 1st end

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0