## NSN 4720-01-341-2336

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-341-2336

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.212 inches  |
| Tempurature Rating:   |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.390 inches  |
| Minimum Inside Bending Radius:  |
| 1.500 inches  |
| End Application:  |
| 1425-01-106-3089  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 11.250 inches   |
| Thread Series Designator:   |
| Unf 1st end   |
| Shelf Life:   |

## NSN 4720-01-341-2336

Nonmetallic Hose Assembly - Page 2 of 2



|  |  |  | ıre: |
|--|--|--|------|
|  |  |  |      |

--

Demilitarization:

No

Fiig:

A542a0