NSN 4720-01-341-6206

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4720-01-341-6206
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.810 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer spirally wrapped steel fabric
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.844 inches 2nd end
Seat Angle:
8.5 degrees 2nd end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:

18.500 inches

NSN 4720-01-341-6206

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0