Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-341-8585

# Cross Sectional Shape:

Round

**Thread Class:** 

3b 1st end

# **Thread Direction:**

Right-hand 1st end

## **Inside Diameter:**

0.375 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.690 inches

Minimum Inside Bending Radius:

#### 2.500 inches

Exterior Color:

Black

### **End Application:**

3930-01-305-2111

#### **Connection Style:**

Swivel nut flare 1st end

## End Connection Design:

Straight 1st end

#### Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Nonskive

### **Burst Test Pressure:**

16000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

4000.0 pounds per square inch

**Thread Size:** 

0.562 inches 2nd end

#### Seat Angle:

37.0 degrees 1st end

## **Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

# Inside Surface Condition:

Smooth

## Measuring Method And Length:

70.000 inches



Media For Which Designed:

Fuel/oil, hydrocarbon single response

# Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A542a0