NSN 4720-01-341-9071

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-341-9071

Cross Sectional Shape:
Round
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Flange Thickness:
0.315 inches 2nd end
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
Flange Outside Diameter:
2.000 inches 2nd end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction: Solid 2nd end
End Connection Design:
Straight 1st end Connection Type:
Connection Type:
Plain face flange 2nd end Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure:
625.0 pounds per square inch
Hydrostatic Test Pressure:
1250.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
54.000 inches
Flange Style:
Round w/ out bolt holes 2nd end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:

N/a

NSN 4720-01-341-9071

Nonmetallic Hose Assembly - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A542a0