Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-342-1338

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
0.625 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Complete niting cadmidin 1st end
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.000 inches working
Special Features:
Inner conveying tube material-rubber, synthetic



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0