Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-342-6765

Cross S	ectional Shape:
Round	
Thread	Class:
3b 1st ei	nd
Thread	Direction:
Right-ha	nd 1st end
Inside D	Diameter:
0.250 in	ches
Tempur	ature Rating:
-40.0 de	grees fahrenheit and 200.0 degrees fahrenheit single response
Outside	Diameter:
0.690 in	ches
Minimu	n Inside Bending Radius:
4.000 in	ches
End Ap	plication:
1055-01	-327-3106
Connec	tion Style:
Swivel n	ut flare 1st end
End Co	nnection Design:
Straight	1st end
Connec	tion Type:
Threade	d internal tube 1st end
Feature	s Provided:
Reusabl	e end fittings
Burst Te	est Pressure:
20000.0	pounds per square inch
Layer C	omposition And Location:
1st layer	braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
Maximu	m Operating Pressure:
5000.0 p	oounds per square inch
Thread	Size:
0.438 in	ches 1st end
Seat An	gle:
37.0 deg	prees 1st end
Hydrost	atic Test Pressure:
10000.0	pounds per square inch
Inside S	Surface Condition:
Smooth	
Measuri	ng Method And Length:
19.000 ii	nches
Media F	or Which Designed:
Fuel/oil,	hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0