

View Online at <https://aerobasegroup.com/nsn/4720-01-342-6772>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

1.156 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Hose Or Tubing Specification/std Data:**

Sae j517, 100r2, type at-81434 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Application:**

3820-01-178-5057

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Connection Type:**

Threaded external pipe 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

9000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided steel wire err-100

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

25.000 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

Sae j517, 100r2, type at-81434 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0