

View Online at <https://aerobasegroup.com/nsn/4720-01-342-6776>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

1.156 inches

Minimum Inside Bending Radius:

9.500 inches

Hose Or Tubing Specification/std Data:

Sae j517, 100r2, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

3820-01-178-5057

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

9000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided steel wire err-100

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

37.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Specification Data:

Sae j517, 100r2, type at-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0