

View Online at <https://aerobasegroup.com/nsn/4720-01-343-5786>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.600 inches and 0.625 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.850 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

90.0

**End Application:**

Mcdonnell douglas, aircraft, model a/f-18

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

3600.0 pounds per square inch

**Layer Composition And Location:**

1st layer woven fabric and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

1800.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

18.000 inches working

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

81343-as620 government standard

**Specification Or Standard:**

2 class and 2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0