

View Online at <https://aerobasegroup.com/nsn/4720-01-343-5786>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.600 inches and 0.625 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

0.850 inches

Minimum Inside Bending Radius:

3.000 inches

Angle Between Rigid Elbow Fittings In Deg:

90.0

End Application:

Mcdonnell douglas, aircraft, model a/f-18

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

3600.0 pounds per square inch

Layer Composition And Location:

1st layer woven fabric and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1800.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Convuluted

Measuring Method And Length:

18.000 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as620 government standard

Specification Or Standard:

2 class and 2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0