Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-344-3951

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-5.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.600 inches
Minimum Inside Bending Radius:
0.750 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and outer layer braided polyester cord
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Inside Surface Condition:
Convoluted
Measuring Method And Length:
17.750 inches
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4720-01-344-3951

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

