NSN 4720-01-346-1709



Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-346-1709

Cross Sectional Shape:
Round

Thread Class:
3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches

Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.585 inches

Minimum Inside Bending Radius: 4.625 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

34.000 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4720-01-346-1709

Nonmetallic Hose Assembly - Page 2 of 2



Demi			

Yes - demil/mli

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-26626 spec.